

# FEKA 300



The FEKA 300 submersible pump is ideal for fixed or portable vertical installations and suitable for pumping clean water containing soft solids up to 30 mm in diameter.

## PUMP FEATURES:

### Compact design

- Portable pump for lifting water from tanks and rivers or emptying swimming pools
- Vertical discharge makes the pump suitable for use in narrow pits

### Protective functions

- Thermal overload protection
- Current overload protection
- Ability to operate when partially submerged

### Complete package

- Supplied with a 10 metre long power cable with plug, self-sealing fitting and 4-step fitting



## OPERATING CONDITIONS:

### Liquid temperature

0°C to +35°C

### Maximum immersion depth

7 metres

### Maximum dry running time

1 minute

## CONSTRUCTION:

### Materials

- Technopolymer pump body, impeller, top body and suction grid
- Stainless steel motor and rotor shaft
- Triple o-ring seals interposed with grease chamber

### Voltage

1 x 240 V, 50 Hz

### Protection level

IP68

### Insulation class

F

## TECHNICAL DATA:

Pump Model	P2 (kW)	1 ph In (A)	Outlet	Weight (kg)	Dimensions (mm)		Max Flow (l/min)	Flow		
					Height	Width		l/min	m <sup>3</sup> /h	0
FEKA 300	0.22	1.5	1 1/4" M	5.8	313	140	124	5.2	2.8	1.0

## PERFORMANCE GRAPH:

